



INDUSTRIAL REFRIGERATION PROS

ABSOLUTE ZERO MIN



NAPHTHENIC MINERAL OIL LUBRICANTS

TYPICAL DATA

		MIN-32	MIN-68	MIN-100
Viscosity @ 40°C	cSt	29.7	60.2	96.8
Viscosity @ 100°C	cSt	4.4	6.5	9.0
Viscosity @ 100°F	SUS	155	316	515
Viscosity @ 210°F	SUS	41	48	56
Viscosity Index		54	52	45
Density 15.6°C (60°F)	g/cm ³	0.907	0.916	0.920
Flash Point	°C (°F)	178 (352)	190 (375)	215 (420)
Pour Point	°C (°F)	-43 (-45)	-34 (-30)	-29 (-20)
Floc Point	°C (°F)	-57 (-70)	-50 (-58)	-39 (-38)
Dielectric Strength	KV	39	35	30
Aniline Point	°C (°F)	79 (174)	84 (183)	91 (197)
Acid Number	mg KOH/g	< 0.05	< 0.05	< 0.05
Color		0.5 (<1.0)	0.5 (< 1.5)	2.0 (< 3.0)
Water Content	ppm	< 35	< 35	< 35
Freon Stability		pass	pass	pass

AZ MIN OILS

AZ MIN Oils are made from premium base stocks and offer optimized solubility in CFC, HCFC, and blended refrigerants. AZ MIN Oils offer exceptional chemical and thermal stability and provide a very long service life.

Typical Property Data is not intended for use as Specifications